


SPECIFICATION:

Contact Rating : 10A125/250VAC TV-8 (A, J) TV-10 (C)
 10A/142A 250VAC~UT85 (A, D, S, N, F)
 Contact Resistance : 50 milliohm max.
 Insulation Resistance : 500 megohms min. 500VDC.
 Withstand Voltage : 2,000 VAC-1 minute
 Endurance : 10,000 Cycles
 Stroke : Lock stroke 2.6±0.5mm
 full stroke 4.2±0.5mm
 Operating Force : 500±200gf
 RoHS Compline

APPROVAL FILE NO:

UL FILE NO: E105856
 CSA FILE NO: 112904
 VDE FILE NO: 40014604
 NEMKO FILE NO: P05203711
 SEMKO FILE NO: 502270
 DEMKO FILE NO: 313272-01
 TCMKO FILE NO: 21532



主要尺寸(*)		重要尺寸	
A1	A	31.2	
B1	B	25.5	
C1	C	18.5	
D1	D	18.8	
E1	E	12.5	
F1	F	20.3	
G1	G	9	
H1	H		
I1	I		
J1	J		

捷森電子工業股份有限公司					DES	P218 SERIES	
TOL	>0.3~6	±0.1	DRW	Z, H, R	2007.01.17	TITLE	PUSH SWITCH
	>6~30	±0.15	DESIGN	Z, H, R	2007.01.17	DWG NO.	PNA-000371
	>30	±0.3	CHECKED		07.2.19	MODEL	P218-21
SCALE		UNI1	APPROVED			VERSION	A2
PK		TOTAL	1	PAGE	1 OF 1		2007.01.20